
Quantum Documentation

Release 2012.2.4-dev

Quantum development team

July 30, 2013

CONTENTS

1	Development Documents	3
1.1	Developer Guide	3
1.2	Open Stack Common	3
1.3	Quantum Sources (modified by POL)	3
1.4	Man Pages	12
	Python Module Index	15
	Index	17

Quantum is an OpenStack project to provide “network connectivity as a service” between interface devices (e.g., vNICs) managed by other Openstack services (e.g., nova). It implements the [Quantum API Guide](#).

This document describes Quantum for contributors of the project, and assumes that you are already familiar with Quantum from an [end-user perspective](#).

This documentation is generated by the Sphinx toolkit and lives in the source tree. Additional documentation on Quantum and other components of OpenStack can be found on the [OpenStack wiki](#). The [Quantum Development wiki](#) is a very good place to start.

Enjoy!

DEVELOPMENT DOCUMENTS

1.1 Developer Guide

The [Quantum Wiki](#) is a very good place to start.

1.2 Open Stack Common

A number of modules used are from the openstack-common project. The imported files are in 'quantum/openstack-common.conf'. More information can be found at [OpenStack Common](#).

1.3 Quantum Sources (modified by POL)

1.3.1 Source: quantum/agent/linux/interface.py

```
class quantum.agent.linux.interface.BridgeInterfaceDriver(conf)
    Bases: quantum.agent.linux.interface.LinuxInterfaceDriver
    Driver for creating bridge interfaces.
    DEV_NAME_PREFIX = 'ns-'
    plug(network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None)
        Plugin the interface.
    unplug(device_name, bridge=None, namespace=None, prefix=None)
        Unplug the interface.
class quantum.agent.linux.interface.LinuxInterfaceDriver(conf)
    Bases: object
    DEV_NAME_LEN = 14
    DEV_NAME_PREFIX = 'tap'
    check_bridge_exists(bridge)
    get_device_name(port)
    init_l3(device_name, ip_cidrs, namespace=None)
        Set the L3 settings for the interface using data from the port. ip_cidrs: list of 'X.X.X.X/YY' strings
```

plug (*network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None*)
Plug in the interface.

unplug (*device_name, bridge=None, namespace=None, prefix=None*)
Unplug the interface.

class `quantum.agent.linux.interface.MetaInterfaceDriver` (*conf*)
Bases: `quantum.agent.linux.interface.LinuxInterfaceDriver`

get_device_name (*port*)

plug (*network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None*)

unplug (*device_name, bridge=None, namespace=None, prefix=None*)

class `quantum.agent.linux.interface.NullDriver` (*conf*)
Bases: `quantum.agent.linux.interface.LinuxInterfaceDriver`

plug (*network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None*)

unplug (*device_name, bridge=None, namespace=None, prefix=None*)

class `quantum.agent.linux.interface.OVSInterfaceDriver` (*conf*)
Bases: `quantum.agent.linux.interface.LinuxInterfaceDriver`

Driver for creating an internal interface on an OVS bridge.

plug (*network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None*)
Plug in the interface.

unplug (*device_name, bridge=None, namespace=None, prefix=None*)
Unplug the interface.

POL New **class** `quantum.agent.linux.interface.OVSLibvirtInterfaceDriver` (*conf*)
Bases: `quantum.agent.linux.interface.OVSInterfaceDriver`

plug (*network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None*)
Plug in the interface.

Param *network_id*: network identifier.

Param *port_id*: port identifier.

Param *device_name*: name of the network interface to create.

Param *mac_address*: MAC address to be set on the new interface.

Param *bridge*: name of the bridge where the interface will be plug.

Param *namespace*: namespace name.

Param *prefix*: namespace prefix.

class `quantum.agent.linux.interface.OVSVethInterfaceDriver` (*conf*)
Bases: `quantum.agent.linux.interface.OVSInterfaceDriver`

Driver for creating an OVS interface using veth.

DEV_NAME_PREFIX = 'ns-'

plug (*network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None*)
Plugin the interface.

unplug (*device_name, bridge=None, namespace=None, prefix=None*)
Unplug the interface.


```
class quantum.agent.linux.interface.RyuInterfaceDriver (conf)
    Bases: quantum.agent.linux.interface.OVSInterfaceDriver

    Driver for creating a Ryu OVS interface.

    plug (network_id, port_id, device_name, mac_address, bridge=None, namespace=None, prefix=None)
        Plug in the interface.
```

1.3.2 Source: quantum/agent/linux/libvirt_config.py **POL New**

Configuration for libvirt objects.

Classes to represent the configuration of various libvirt objects and support conversion to/from XML

```
class quantum.agent.linux.libvirt_config.LibvirtConfigNetwork (**kwargs)
    Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject

    add_tunnel (tunnel)
        Set LibvirtConfigNetworkTunnel XML object.

        Parameters tunnel – LibvirtConfigNetworkTunnel XML object.

    format_dom ()
        Return LibvirtConfigNetwork XML object.

    set_bridge (br)
        Set LibvirtConfigNetworkBridge XML object.

        Parameters br – LibvirtConfigNetworkBridge XML object.

    set_forward (fwd)
        Set LibvirtConfigNetworkForward XML object.

        Parameters fwd – LibvirtConfigNetworkForward XML object.

    set_ip (ip)
        Set LibvirtConfigNetworkIP XML object.

        Parameters ip – LibvirtConfigNetworkIP XML object.

    set_portgroup (portgroup)
        Set LibvirtConfigNetworkPortGroup XML object.

        Parameters portgroup – LibvirtConfigNetworkPortGroup XML object.

class quantum.agent.linux.libvirt_config.LibvirtConfigNetworkBridge (**kwargs)
    Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject

    Generate bridge block of XML network configuration.

    format_dom ()
        Return LibvirtConfigNetworkBridge XML object.

class quantum.agent.linux.libvirt_config.LibvirtConfigNetworkDHCP (**kwargs)
    Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject

    Generate DHCP block of XML network configuration.

    format_dom ()
        Return LibvirtConfigNetworkDHCP XML object.

class quantum.agent.linux.libvirt_config.LibvirtConfigNetworkForward (**kwargs)
    Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject

    Generate forward block of XML network configuration.
```

format_dom()
Return LibvirtConfigNetworkForward XML object.

class quantum.agent.linux.libvirt_config.**LibvirtConfigNetworkIP** (**kwargs)
Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject
Generate IP block of XML network configuration.

format_dom()
Return LibvirtConfigNetworkIP XML object.

set_dhcp(dhcp)

class quantum.agent.linux.libvirt_config.**LibvirtConfigNetworkPortGroup** (**kwargs)
Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject
Generate port group block of XML network configuration.

add_vport_param(key, value)
Add a virtual port parameter.

Parameters

- **key** – virtual port key.
- **value** – virtual port value.

format_dom()
Return LibvirtConfigNetworkPortGroup XML object.

set_vlan(vlan)
Set VLAN XML object.

Parameters **vlan** – LibvirtConfigNetworkVlan XML object.

class quantum.agent.linux.libvirt_config.**LibvirtConfigNetworkTunnel** (**kwargs)
Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject

format_dom()
Return LibvirtConfigNetworkTunnel XML object.

class quantum.agent.linux.libvirt_config.**LibvirtConfigNetworkVlan** (**kwargs)
Bases: quantum.agent.linux.libvirt_config.LibvirtConfigObject
Generate vlan block of XML network configuration.

add_vlan_tag(tag)
Add a VLAN tag.

Parameters **tag** – VLAN tag to add.

format_dom()
Return LibvirtConfigNetworkVlan XML object.

class quantum.agent.linux.libvirt_config.**LibvirtConfigObject** (**kwargs)
Bases: object

Taken from nova/virt/libvirt/config.py.

format_dom()

parse_dom(xmldoc)

parse_str(xmlstr)

to_xml(pretty_print=True)

1.3.3 Source: quantum/agent/linux/libvirt_lib.py **POL New**

class quantum.agent.linux.libvirt_lib.Libvirt (*read_only=False, libvirt_type='qemu'*)
Taken from nova/virt/libvirt/config.py.

has_min_version (*ver*)

init_host (*host*)

uri

quantum.agent.linux.libvirt_lib.patch_tpool_proxy()
eventlet.tpool.Proxy doesn't work with old-style class in `__str__()` or `__repr__()` calls. See bug #962840 for details. We perform a monkey patch to replace those two instance methods.

1.3.4 Source: quantum/agent/rpc.py

class quantum.agent.rpc.NotificationDispatcher
Bases: object

run_dispatch (*handler*)

class quantum.agent.rpc.PluginApi (*topic*)
Bases: quantum.openstack.common.rpc.proxy.RpcProxy

Agent side of the rpc API.

API version history: 1.0 - Initial version.

BASE_RPC_API_VERSION = '1.0'

get_device_details (*context, device, agent_id*)

POL New **get_network_binding** (*context, network_id, agent_id*)

Abstract method to retrieve the binding between a virtual network and its physical realization.

Parameters

- **context** – RPC context.
- **network_id** – network identifier.
- **agent_id** – agent identifier.

Returns requested network binding.

tunnel_sync (*context, tunnel_ip*)

update_device_down (*context, device, agent_id*)

update_device_up (*context, device, agent_id*)

quantum.agent.rpc.create_consumers (*dispatcher, prefix, topic_details*)
Create agent RPC consumers.

Parameters

- **dispatcher** – The dispatcher to process the incoming messages.
- **prefix** – Common prefix for the plugin/agent message queues.
- **topic_details** – A list of topics. Each topic has a name and a operation.

Returns A common Connection.

1.3.5 Source: quantum/plugins/ovs_quantum_plugin.py

POL Mod `class quantum.plugins.openvswitch.ovs_quantum_plugin.AgentNotifierApi(topic)`
Bases: `quantum.openstack.common.rpc.proxy.RpcProxy`

Agent side of the linux bridge rpc API.

API version history: 1.0 - Initial version.

POL modification: send notifications for two new events (network_create, port_create).

BASE_RPC_API_VERSION = '1.0'

POL New `network_create(context, network_id, segmentation_id)`
Send network_create event.

Parameters

- **context** – RPC context.
- **network_id** – network identifier.
- **segmentation_id** – segmentation identifier (e.g. VLAN ID).

`network_delete(context, network_id)`

POL New `port_create(context, port, network_type, segmentation_id, physical_network)`
Send port_create event.

Parameters

- **context** – RPC context.
- **port** – port identifier.
- **network_type** – network type (e.g. VLAN, GRE, FLAT).
- **segmentation_id** – segmentation identifier (e.g. VLAN ID).
- **physical_network** – name of physical network.

`port_update(context, port, network_type, segmentation_id, physical_network)`

`tunnel_update(context, tunnel_ip, tunnel_id)`

class `quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2(configfile=None)`
Bases: `quantum.db.db_base_plugin_v2.QuantumDbPluginV2`,
`quantum.db.l3_db.L3_NAT_db_mixin`

Implement the Quantum abstractions using Open vSwitch.

Depending on whether tunneling is enabled, either a GRE tunnel or a new VLAN is created for each network. An agent is relied upon to perform the actual OVS configuration on each host.

The provider extension is also supported. As discussed in <https://bugs.launchpad.net/quantum/+bug/1023156>, this class could be simplified, and filtering on extended attributes could be handled, by adding support for extended attributes to the QuantumDbPluginV2 base class. When that occurs, this class should be updated to take advantage of it.

POL Mod `create_network(context, network)`
Create a virtual network.

Parameters

- **context** – RPC context.
- **network** – network object.

POL modification: send network_create event to agents.

POL New `create_port (context, port)`

Create a new port on a virtual network.

Parameters

- **context** – RPC context.
- **port** – port object.

Returns port object.

`delete_network (context, id)`

`delete_port (context, id, l3_port_check=True)`

`get_network (context, id, fields=None)`

`get_networks (context, filters=None, fields=None)`

`setup_rpc ()`

`supported_extension_aliases = ['provider', 'router']`

`update_network (context, id, network)`

`update_port (context, id, port)`

`class quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks (rpc_context, notifier)`

Bases: `quantum.db.dhcp_rpc_base.DhcpRpcCallbackMixin`

`RPC_API_VERSION = '1.0'`

`create_rpc_dispatcher ()`

Get the rpc dispatcher for this manager.

If a manager would like to set an rpc API version, or support more than one class as the target of rpc messages, override this method.

`get_device_details (rpc_context, **kwargs)`

Agent requests device details

POL New `get_network_binding (rpc_context, **kwargs)`

Retrieve the binding between a virtual network and its physical realization.

Parameters

- **rpc_context** – RPC context.
- **kwargs** – additional arguments.

Returns requested network binding.

`tunnel_sync (rpc_context, **kwargs)`

Update new tunnel.

Updates the database with the tunnel IP. All listening agents will also be notified about the new tunnel IP.

`update_device_down (rpc_context, **kwargs)`

Device no longer exists on agent

1.3.6 Source: quantum/plugins/openvswitch/common/config.py **POL Mod**

POL modifications:

- added local_interface parameter to ovs_opts.
- added libvirt_type parameter to agent_opts.

1.3.7 Source: quantum/plugins/openvswitch/agent/ovs_libvirt_quantum_agent.py **POL New**

class quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent (*local_ip,*
lo-
cal_interface,
bridge_mapping,
root_helper,
polling_interval,
re-
con-
nect_interval,
rpc,
en-
able_tunneling,
lib-
virt_type)

Bases: object

Implements OVS-based tunneling, VLANs and flat networks.

Two local bridges are created: an integration bridge (defaults to 'br-int') and a tunneling bridge (defaults to 'br-tun'). An additional bridge is created for each physical network interface used for VLANs and/or flat networks.

All VM VIFs are plugged into the integration bridge. VM VIFs on a given virtual network share a common "local" VLAN (i.e. not propagated externally). The VLAN id of this local VLAN is mapped to the physical networking details realizing that virtual network.

For virtual networks realized as GRE tunnels, a Logical Switch (LS) identifier and is used to differentiate tenant traffic on inter-HV tunnels. A mesh of tunnels is created to other Hypervisors in the cloud. These tunnels originate and terminate on the tunneling bridge of each hypervisor. Port patching is done to connect local VLANs on the integration bridge to inter-hypervisor tunnels on the tunnel bridge.

For each virtual networks realized as a VLANs or flat network, a veth is used to connect the local VLAN on the integration bridge with the physical network bridge, with flow rules adding, modifying, or stripping VLAN tags as necessary.

MAX_VLAN_TAG = 4094

MIN_VLAN_TAG = 1

RPC_API_VERSION = '1.0'

create_rpc_dispatcher()

Get the rpc dispatcher for this manager.

If a manager would like to set an rpc API version, or support more than one class as the target of rpc messages, override this method.

daemon_loop(db_connection_url)

Main loop.

network_create (*context*, ***kwargs*)

Handle network_create event.

Parameters *kwargs* – event arguments

network_delete (*context*, ***kwargs*)

Handle network_delete event

port_create (*context*, ***kwargs*)

Handle port_create event.

Parameters *kwargs* – event arguments

rpc_loop ()

setup_backbone_network ()

Create the Backbone Network.

Returns virNetwork Libvirt object for Backbone Network.

setup_rpc ()

Setup RPC for communication with Quantum server.

setup_tunnel (*tunnel_ip*, *tunnel_id*)

Add a tunnel to the Backbone Network.

Parameters

- **tunnel_ip** – remote endpoint's IP.
- **tunnel_id** – tunnel identifier associated to this host.

setup_tvd_network (*network_id*, *segmentation_id*)

Create a TVD network.

Parameters

- **network_id** – network identifier.
- **segmentation_id** – segmentation identifier (e.g. VLAN ID)

start_tvd_networks ()

Start already defined TVD networks.

tunnel_sync ()

Execute tunnels synchronization with Quantum server.

Returns resync flag

tunnel_update (*context*, ***kwargs*)

Handle tunnel_update event.

Parameters *kwargs* – event arguments

`quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.create_network_conf` (*network_type=*

net-
work_id=None,
source-
bridge=None,
vlan_id=None)

Create XML configuration of a network.

Parameters

- **network_type** – backbone/tvd.
- **network_id** – network identifier.

- **sourcebridge** – name of the backbone bridge (tvd network only).
- **vlan_id** – VLAN identifier.

Returns LibvirtConfigNetwork object.

```
quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.create_tunnel_conf(tunnel_ip,  
                                                                           tun-  
                                                                           nel_id)
```

Create XML configuration of a tunnel.

Parameters

- **tunnel_ip** – remote endpoint's IP.
- **tunnel_id** – tunnel ID associated to this host.

Returns LibvirtConfigNetworkTunnel object.

```
quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.create_tvd_portgroup(vlan_id)
```

Create XML configuration of a port group with type openvswitch.

Parameters **vlan_id** – VLAN identifier.

Returns LibvirtConfigNetworkPortGroup object.

```
quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.main()
```

1.4 Man Pages

1.4.1 quantum-server

Quantum Server

Author openstack@lists.launchpad.net

Date 2012-04-05

Copyright OpenStack LLC

Version 2012.1

Manual section 1

Manual group cloud computing

SYNOPSIS

```
quantum-server [options]
```

DESCRIPTION

quantum-server provides a webserver that exposes the Quantum API, and passes all webservice calls to the Quantum plugin for processing.

OPTIONS

--version	show program's version number and exit
-h, --help	show this help message and exit
-v, --verbose	Print more verbose output
-d, --debug	Print debugging output
--config-file=PATH	Path to the config file to use, for example, /etc/quantum/quantum.conf. When not specified (the default), we generally look at the first argument specified to be a config file, and if that is also missing, we search standard directories for a config file. (/etc/quantum/, /usr/lib/pythonX/site-packages/quantum/)

Logging Options: The following configuration options are specific to logging functionality for this program.

--log-config=PATH	If this option is specified, the logging configuration file specified is used and overrides any other logging options specified. Please see the Python logging module documentation for details on logging configuration files.
--log-date-format=FORMAT	Format string for %(asctime)s in log records. Default: %Y-%m-%d %H:%M:%S
--use-syslog	Output logs to syslog.
--log-file=PATH	(Optional) Name of log file to output to. If not set, logging will go to stdout.
--log-dir=LOG_DIR	(Optional) The directory to keep log files in (will be prepended to --logfile)

FILES

plugins.ini file contains the plugin information quantum.conf file contains configuration information in the form of python-gflags.

SEE ALSO

- [OpenStack Quantum](#)

BUGS

- Quantum is sourced in Launchpad so you can view current bugs at [OpenStack Bugs](#)

PYTHON MODULE INDEX

a

`quantum.agent.linux.interface`, 3
`quantum.agent.linux.libvirt_config`, 5
`quantum.agent.linux.libvirt_lib`, 7
`quantum.agent.rpc`, 7

p

`quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent`,
10
`quantum.plugins.openvswitch.common.config`,
10
`quantum.plugins.openvswitch.ovs_quantum_plugin`,
8

INDEX

A

`add_tunnel()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetwork method), 5

`add_vlan_tag()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkVlan method), 6

`add_vport_param()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkPortGroup method), 6

`AgentNotifierApi` (class in quantum.plugins.openvswitch.ovs_quantum_plugin), 8

B

`BASE_RPC_API_VERSION` (quantum.agent.rpc.PluginApi attribute), 7

`BASE_RPC_API_VERSION` (quantum.plugins.openvswitch.ovs_quantum_plugin.AgentNotifierApi attribute), 8

`BridgeInterfaceDriver` (class in quantum.agent.linux.interface), 3

C

`check_bridge_exists()` (quantum.agent.linux.interface.LinuxInterfaceDriver method), 3

`create_consumers()` (in module quantum.agent.rpc), 7

`create_network()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2 method), 8

`create_network_conf()` (in module quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 11

`create_port()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2 method), 9

`create_rpc_dispatcher()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 10

`create_rpc_dispatcher()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks method), 9

`create_tunnel_conf()` (in module quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

`create_vtd_portgroup()` (in module quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

D

`daemon_loop()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent method), 10

`delete_network()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2 method), 9

`delete_port()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2 method), 9

`DEV_NAME_LEN` (quantum.agent.linux.interface.LinuxInterfaceDriver attribute), 3

`DEV_NAME_PREFIX` (quantum.agent.linux.interface.BridgeInterfaceDriver attribute), 3

`DEV_NAME_PREFIX` (quantum.agent.linux.interface.LinuxInterfaceDriver attribute), 3

`DEV_NAME_PREFIX` (quantum.agent.linux.interface.OVSVethInterfaceDriver attribute), 4

`format_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetwork method), 5

`format_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkBridge method), 5

`format_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkDomain method), 5

`format_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkFormat method), 5

`format_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkIP method), 6

`format_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkPort method), 6

format_dom() (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkTunnel (class in quantum.agent.linux.libvirt_config), 6
 method), 6
 format_dom() (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkVlan (class in quantum.agent.linux.libvirt_config), 6
 method), 6
 format_dom() (quantum.agent.linux.libvirt_config.LibvirtConfigObject (class in quantum.agent.linux.libvirt_config), 6
 method), 6

G

get_device_details() (quantum.agent.rpc.PluginApi (class in quantum.agent.rpc), 7
 method), 7

get_device_details() (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 9
 method), 9

get_device_name() (quantum.agent.linux.interface.LinuxInterfaceDriver (class in quantum.agent.linux.interface), 3
 method), 3

get_device_name() (quantum.agent.linux.interface.MetaInterfaceDriver (class in quantum.agent.linux.interface), 4
 method), 4

get_network() (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 9
 method), 9

get_network_binding() (quantum.agent.rpc.PluginApi (class in quantum.agent.rpc), 7
 method), 7

get_network_binding() (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 9
 method), 9

get_networks() (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 9
 method), 9

H

has_min_version() (quantum.agent.linux.libvirt_lib.Libvirt (class in quantum.agent.linux.libvirt_lib), 7
 method), 7

I

init_host() (quantum.agent.linux.libvirt_lib.Libvirt (class in quantum.agent.linux.libvirt_lib), 7
 method), 7

init_l3() (quantum.agent.linux.interface.LinuxInterfaceDriver (class in quantum.agent.linux.interface), 3
 method), 3

L

Libvirt (class in quantum.agent.linux.libvirt_lib), 7

LibvirtConfigNetwork (class in quantum.agent.linux.libvirt_config), 5

LibvirtConfigNetworkBridge (class in quantum.agent.linux.libvirt_config), 5

LibvirtConfigNetworkDHCP (class in quantum.agent.linux.libvirt_config), 5

LibvirtConfigNetworkForward (class in quantum.agent.linux.libvirt_config), 5

LibvirtConfigNetworkIP (class in quantum.agent.linux.libvirt_config), 6

LibvirtConfigNetworkPortGroup (class in quantum.agent.linux.libvirt_config), 6

M

main() (in module quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

MAX_VLAN_TAG (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 10
 attribute), 10

MetaInterfaceDriver (class in quantum.agent.linux.interface), 4

MIN_VLAN_TAG (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 10
 attribute), 10

network_create() (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 10
 method), 10

network_delete() (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 11
 method), 11

network_delete() (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 11
 method), 11

NotificationDispatcher (class in quantum.agent.rpc), 7

NullDriver (class in quantum.agent.linux.interface), 4

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

OVSRpcCallbacks (class in quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent), 12

P

`parse_dom()` (quantum.agent.linux.libvirt_config.LibvirtConfigObject method), 6

`parse_str()` (quantum.agent.linux.libvirt_config.LibvirtConfigObject method), 6

`patch_tpool_proxy()` (in module quantum.agent.linux.libvirt_lib), 7

`plug()` (quantum.agent.linux.interface.BridgeInterfaceDriver method), 3

`plug()` (quantum.agent.linux.interface.LinuxInterfaceDriver method), 3

`plug()` (quantum.agent.linux.interface.MetaInterfaceDriver method), 4

`plug()` (quantum.agent.linux.interface.NullDriver method), 4

`plug()` (quantum.agent.linux.interface.OVSInterfaceDriver method), 4

`plug()` (quantum.agent.linux.interface.OVSLibvirtInterfaceDriver method), 4

`plug()` (quantum.agent.linux.interface.OVSVethInterfaceDriver method), 4

`plug()` (quantum.agent.linux.interface.RyuInterfaceDriver method), 5

`PluginApi` (class in quantum.agent.rpc), 7

`port_create()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`port_create()` (quantum.plugins.openvswitch.ovs_quantum_plugin.AgentNotificationApi method), 8

`port_update()` (quantum.plugins.openvswitch.ovs_quantum_plugin.AgentNotificationApi method), 8

Q

quantum.agent.linux.interface (module), 3

quantum.agent.linux.libvirt_config (module), 5

quantum.agent.linux.libvirt_lib (module), 7

quantum.agent.rpc (module), 7

quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent (module), 10

quantum.plugins.openvswitch.common.config (module), 10

quantum.plugins.openvswitch.ovs_quantum_plugin (module), 8

R

`RPC_API_VERSION` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent attribute), 10

`RPC_API_VERSION` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks attribute), 9

`rpc_loop()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`run_dispatch()` (quantum.agent.rpc.NotificationDispatcher method), 7

`RyuInterfaceDriver` (class in quantum.agent.linux.interface), 4

S

`set_bridge()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetwork method), 5

`set_dhcp()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkIP method), 6

`set_forward()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetwork method), 5

`set_ip()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetwork method), 5

`set_portgroup()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetwork method), 5

`set_vlan()` (quantum.agent.linux.libvirt_config.LibvirtConfigNetworkPortGroup method), 6

`setup_backbone_network()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`setup_rpc()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`setup_rpc()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumAgent method), 9

`setup_tunnel()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`setup_tvd_network()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`start_in_AgentWorkSpace()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`supported_extension_aliases` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPlugin attribute), 9

T

`xml()` (quantum.agent.linux.libvirt_config.LibvirtConfigObject method), 6

`tunnel_sync()` (quantum.agent.rpc.PluginApi method), 7

`tunnel_sync()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`tunnel_sync()` (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks method), 9

`tunnel_update()` (quantum.plugins.openvswitch.agent.ovs_libvirt_quantum_agent.OVSQuantumAgent method), 11

`unplug()` (quantum.plugins.openvswitch.ovs_quantum_plugin.AgentNotificationApi method), 8

U

`unplug()` (quantum.agent.linux.interface.BridgeInterfaceDriver method), 3

`unplug()` (quantum.agent.linux.interface.LinuxInterfaceDriver method), 4

unplug() (quantum.agent.linux.interface.MetaInterfaceDriver
method), 4

unplug() (quantum.agent.linux.interface.NullDriver
method), 4

unplug() (quantum.agent.linux.interface.OVSInterfaceDriver
method), 4

unplug() (quantum.agent.linux.interface.OVSVethInterfaceDriver
method), 4

update_device_down() (quantum.agent.rpc.PluginApi
method), 7

update_device_down() (quan-
tum.plugins.openvswitch.ovs_quantum_plugin.OVSRpcCallbacks
method), 9

update_device_up() (quantum.agent.rpc.PluginApi
method), 7

update_network() (quan-
tum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2
method), 9

update_port() (quantum.plugins.openvswitch.ovs_quantum_plugin.OVSQuantumPluginV2
method), 9

uri (quantum.agent.linux.libvirt_lib.Libvirt attribute), 7